



Technical Impacts of Large Scale Wind Penetration on Electric Power Systems – Roadmap for Greece and Coordinated Activities in South Eastern Europe

J. Kabouris

**Director for Planning - Hellenic Transmission System Operator
Convener of ENTSO-E RG South-East Continental Europe**

WIND POWER

- **The most promising source for achieving 20% of RES penetration**
- **Is becoming fast a major primary source than a marginal**
- **Main Energy Policy line in EU**
- **Support policies (priority to dispatch, fixed feed-in tariffs, etc.)**
- **WFs are expected to have the largest share**

THE TSO POINT OF VIEW

Large wind penetration

- Technically a new challenge
- Impact on ESI economics and the Market

Key issue:

- volatility and uncontrollability of primary energy
- Low availability
- Random nature of wind
- Significant TECHNICAL and ECONOMIC impacts are expected

CRUCIAL TECHNICAL ISSUES

- Load following (automatic generation control and frequency regulation)
- Coordination with conventional thermal generators
- Transmission capacities
- Monitoring and Control by Energy Management Systems
- Voltage regulation (in HV and MV level)
- WF behavior in normal operation and during contingencies
- Impacts on electricity exchanges and trading
- **TSOs should be prepared to face these challenges**

OTHER ISSUES

- Impact on static stability (reduced frequency oscillation modes and impact on system damping).
- Impact of hydro thermal scheduling
- Increase of short circuit power at the points of connection
- Protection resetting in the distribution network

LOAD FOLLOWING & FREQUENCY REGULATION (I)

- Random primary energy of high volatility
- $P=L$ to achieve «constant» frequency
- Need to follow the load variations. Today WFs do not contribute to Automatic Generation Control
- Increased needs for reserves (especially secondary and tertiary) under high wind penetration
- Increased cost of reserves
- Increased flexibility of conventional generators is required to minimize wind power curtailments

LOAD FOLLOWING & FREQUENCY REGULATION (II)

Modern WTGs are capable to contribute to AGC through:

- Fast pitch actions
- Switched loads
- Speed regulation of wind turbines with power electronic interface

COORDINATION WITH CONVENTIONAL THERMAL GENERATORS


- Technical minimum (usually a hard constraint)
- Ramp up / down rates
- Start up / shut down times
- Avoid often start / stop of steam and CC generators
- Need for more peaking power (hydros, open cycle gas turbines)


EXAMPLE: GREECE

Production-mix

Type	Net capacity (MW)	Technical minimum (MW)
Thermal generation	7980	4458
<i>Lignite</i>	4808	2841
<i>Oil</i>	718	430
<i>Natural Gas</i>	1532	1087
<i>Gas turbines</i>	922	
Hydro Generation	3057	
<i>With reservoirs</i>	2442	
<i>Pump storage</i>	615	
RES	771	
<i>Wind</i>	640	
<i>Small Hydro</i>	100	
<i>Biomass-Biogas</i>	31	
Co-generation	113	
Total	11921	4458







Transmission capacities

- Transmission capacities needed from wind areas to the System boundaries.
- In windy areas human activity is limited, i.e. weak network infrastructures
- Cost issues
 - Who bears the cost?
 - Licensing, Authorization/land use
 - Construction
- Spatial distribution of WFs at the planning phase is crucial
- Delays in transmission projects materialization due to time consuming licensing procedures and strong protest

VOLTAGE REGULATION

Local Problem especially with asynchronous WTGs (absence of self-excitation)


Extended use of:

- Capacitors mechanically switched
- SVCs (in extreme cases i.e. off-shore, long connection lines)
- PWM technology offers interesting possibilities for power factor regulation and voltage support.
- Voltage stability is a crucial issue for areas with high wind penetration

WTG behavior during Contingencies

- Under low penetration (current practice):
WTGs tripped during faults leading to low voltages (e.g. u/v protection 0,8 pu for 80 msec)
- Large penetration:
Need to keep WTGs in synchronism and to avoid losing large wind production
- WTGs must have fault ride-through capability i.e. to sustain in operation when very low voltages occur (during transients)
 - It is already required in several countries
 - Already available by the main constructors
 - Extremely crucial for system security

Three-phase short circuit in Larymna substation (150kV)



Red : $0 < V < 0.4 \text{ pu}$


Yellow : $0.4 < V < 0.6 \text{ pu}$

Blue : $0.6 < V < 0.8 \text{ pu}$


LVRT Definition

Requirement of Fault Ride-Through Capability during Voltage Drops in Transmission System

Indicative Low Voltage Ride Through Capability Curve



Comparison of LVRT Requirements



Proposed solutions

- Increase flexibility of conventional generators
- Storage options:
 - develop pump-storage hydros
 - use of electric cars
 - hydrogen economy (future option)
- Improve WTGs to achieve behavior “close” to conventional generators:
 - Contribution to frequency and voltage regulation
 - FRT capability
- Improved wind forecasts
- Increased spatial distribution during planning phase

Roadmap for Greece

Crucial issues

- Approval of WFs by local societies
- Increase of available transmission capacity
- Interconnection of Aegean islands
- Assessment of technical impact of large wind penetration and measures
- Impact on Electricity Markets and costs
- Wind prognosis
- Technical requirements for WFs


New Law for RES

- Calls for 40% RES contribution in electricity
- Simplifies and accelerates the licensing procedure
- Provisions for off-shore WFs
- Exploitation of wind potential of islands
- Expected to come in force within next weeks

HTSO estimates that 6-9 GW of wind capacity is needed to meet the target (depending on the load evolution and other RES development).


The official trajectory towards the target will be officially published on June

National Transmission Development Plan – Increase of available transmission capacity




Projects		
	Existing	Planned
150kV OHL (km)	11467	1000
400kV OHL (km)	4420	820
150kV S/S	284	130
400kV S/S	18	12
Cables 150kV (km)	267	120
Cables 400kV (km)	4	85

It is expected that after the realization of the planned projects at least **8.5 MW** of wind power can be transmitted





- **Interconnection of Syros, Naxos, Mykonos, Paros with mainland through 150 kV cables of 250 km total length**
- **Capacity to connect 150- 200 MW**
- **Licensing has been completed**
- **Tender in public consultation**



Aegean interconnections Long term plan

- Applications for production licenses on the islands
3.095MW, off-shore **3534 MW**
- Preliminary studies on going
- Total length of undersea cables
more than 1500 km
- DC or AC

**Estimated total cost
3-4 bn Euros**



Assessment of impacts



- Detailed studies have been launched to assess the increase of high wind penetration
- Impacts on the electricity market and costs
- Optimization of future generation mix to maximize wind power absorption
- Optimization of operation
- Estimation of wind power curtailments due to system constraints

Greek Grid Code future provisions for WTs

- Contribution to voltage regulation
- Contribution to frequency regulation
- Voltage support during system faults
- Wind Parks Communication interface (necessary signals exchanged with Dispatching Centers)
- Power quality requirements
- Certification and monitoring

Wind Power Forecasting

- Pilot application since August 2008
- Improvements and tuning of the model
- Based on Meteorological Forecast data and on on-site measurements
- Status : Tested/ tuned at Dispatching center
- Prediction : Good / Problems at high Production Hours
- To be integrated in the EMS procedures and tools




MONITORING & CONTROL

- Need for monitoring and control in real time – large amount of measurements
- High penetration may lead to curtailment of wind power under specific system conditions to ensure security
- Extended telecommunication infrastructure
- Bi-directional interface EMS – WF
- Extension of SCADA
- State estimation
- New S/W needed in EMSs , e.g. State Estimators
- Decentralized control-local CCs ?
- Market operation procedures, organization and tools




Integration in the Energy Management System

In the Real Time




Integration in the Market Procedures

In the Day Ahead



Activities for RES development in the Balkan Region



entsoe

The map displays the interconnected network of Continental Europe, showing a dense web of red and blue lines representing various transport routes across the continent. The map includes a legend, a scale bar, and a date stamp (01.07.2009).

Legend

Nodes and edges:

- Nodes:
 - Major nodes (red dots)
 - Minor nodes (blue dots)
- Edges:
 - Major edges (red lines)
 - Minor edges (blue lines)

Other symbols:

- Green lines: National roads
- Yellow lines: International roads
- Orange lines: Air routes
- Blue lines: Sea routes
- Black lines: Railways
- Grey lines: Pipelines
- Green lines: Power lines
- Blue lines: Gas lines
- Red lines: Water supply lines
- Yellow lines: Telecommunications lines
- Black lines: Other infrastructure

Scale: 0 to 1000 km

Date: 01.07.2009

South Eastern Regional Group (CSE) of ENTSO-E



The EWIS project

- EC project to assess the transmission needs in Continental Europe to increase wind power
- 15 TSOs participated (ELIA, CEPS, ENERGINET, TRANSPOWER, AMPRION GmbH, 50Hz Transmission GmbH, EirGrid, HTSO, National Grid, PSE-Operator, Red Electrica de Espana, Rede Electrica Nationalis, RTE , TenneT, Verbund)
- Specific reinforcements have been proposed
- Maximum and minimum load snapshots have been studied
- Balkan area has not been studied in detail
- Inadequate conclusions (only for Greece)
- Started at 5/2007 ended at 4/2010



Ten Year Network Development Plan for European Transmission System (TYNDP)

available on www.entsoe.eu

- 1st edition on June 2010 – Public consultation 1st – 20th April
- Projects of «European Interest » focusing on the interconnections

Main drivers :

- Generation integration – especially RES
- Electricity market development
- Security of supply
- Increase interconnectors' capacity


Grid reinforcement needs for Balkan systems up to 2015



	Demand growth		Low cross border capacity, limited transfer capability of the network
	Future generation evacuation		High short circuit current, need for reactive power, etc.
	Existing generation evacuation		Aging/obsolescence of network equipment
	Generation decommissioning		Major power flow
	Change in exchange patterns		
	Isolated systems to be connected		

The most significant reinforcement projects for this period appear in Greece (Peloponnese, Thrace, Evia etc) and in south Italy.

Grid reinforcement needs for Balkan systems after 2015





Major reinforcement projects for this period appear also in other Balkan countries e.g. Bulgaria, Romania

New projects in Balkan up to 2015


New important electric lines :

- 1) N. Santa (GR)-Maritsa (BG)
- 2) Ernestinovo (HR)-Pecs (HU)
- 3) Stip (MK) – Nis (RS)
- 4) Podgorica (ME)-Tirana (Al)
- 5) Italy-Montenegro (DC)
- 6) Italy-Albania (DC)




	AC 400 kV components
	AC 330 kV components
	AC 225 kV components
	AC 150 kV components
	AC < 150 kV components
	DC components

New projects in Balkan after 2015



New important electric lines :

- 1) Cirkovce (SI)- Heviz (Hu)
- 2) Pancevo (RS)-Resita(RO)
- 3) Okroglo(SI)- Udine(IT)
- 4) Italy – Greece new dc cable

	AC 400 kV components
	AC 330 kV components
	AC 225 kV components
	AC 150 kV components
	AC < 150 kV components
	DC components

Turkey connection



Through 3 400kV interconnection lines :

- Maritsa 3 – Hamitabat (line 1)
- Maritsa 3 – Hamitabat (line 2)
- N. Santa- Babaeski (line 3)

Studies:

- 1st phase : static & dynamic
- 2nd phase: dynamic performance tests and required improvements in TR (frequency control)

To start trial operation in 2010

ENTSO-E effort to establish common Requirements for Generators for Grid Connection and Access

- The requirements shall apply to all new Generating Units above a specific size.

These requirements can be classified as :

- General requirements that apply for all type of Power Generating Facilities connected to the Network
- Requirements for Synchronous Generator Units directly connected to the onshore Network
- Requirements for Power Park Modules, which are technologies not based on a synchronous generator directly connected to the Network (Wind Parks, Solar power stations etc)
- Requirements for offshore generators, includes all technologies connected to an offshore Network.

Common activities for large RES penetration in SE Europe

- Regular meetings for regional issues
- Regular information exchange for RES developments and prospects in each country
- Analysis of the current situation, regulatory and technical frameworks as well as the expected RES penetration in the area.
- Common studies have been launched to assess the impacts of the expected RES penetration in the Balkan grid.
- Detection of weak network points and proposals for reinforcements
- A coordinated Regional Transmission Plan will be issued on 2011
- Establish a regional “wind market”?

Conclusions

- Wind is the most promising source to meet the 3x20 targets
- Wind integration sets a series of technical challenges
- A roadmap to meet the targets for Greece has been set by the HTSO
- Regulatory changes in progress
- Major transmission projects have been planned
- Need for further studies and coordinated activities in the Balkan region
- ENTSO-E is a key player to commonly achieve the goals in a pan-European level.